



Unit (单位): mm

Type 型号	Dimension / 主要尺寸					Basic Load Rating 基本额定负载		Limit Speed 许用转速 min^{-1}	Abutment & Fillet / 推荐的安装尺寸				Mass 重量 (g)	Type 型号
	I.D. 内径 ϕd	O.D. 外径 ϕD	Width 宽度 B	Chamfer (min.) / 倒角尺寸(最小)		Cr (N)	Cor (N)		Db max. 最大	db min. 最小	Rb max. 最大	rb max. 最大		
				r1	R1									
602HZZ	2	7	3.5	0.15	0.15	320	102	63,000	6.25	3.85	0.15	0.15	0.6	602HZZ
623HZZ	3	10	4	0.15	0.15	535	175	50,000	7.98	4.35	0.15	0.15	1.7	623HZZ
624HZZ	4	13	5	0.20	0.20	1110	390	40,000	11.35	6.0	0.20	0.20	3.1	624HZZ
B6-113HZZ1	6	15	6	0.20	0.20	1470	535	40,000	13.3	7.9	0.20	0.20	4.3	B6-113HZZ1
606HZZ1	6	17	6	0.30	0.30	1920	670	38,000	14.8	8.2	0.30	0.30	6.1	606HZZ1

注1) 深沟球轴承 (ISC制) 采用不锈钢材质, 并注入有低起尘润滑脂 (NSK LG2), 是无尘规格的轴承。

Note 1) Deep Groove Ball Bearings (manufactured by ISC) are designed for clean room use, they are made of Stainless steel with low contamination grease (NSK LG2) packed.